

Power Units for ACs & Pumps

Power Units for ACs & Pumps

Ideal aesthetics for domestic interiors. Gels completely with all other switch plates

Ease of mounting on North-West modular plates, bakelite sheets for flush type mounting

Box type version can be mounted with North-West surface boxes

Overload protection covering a wide current range

Silver touch contacts for very high current carrying capacity

Convenience of current setting, ample wiring space and shrouding to prevent any accidental contact

All live metal parts are covered with non-inflammable Thermo set material

Perma-fit mounting for strength and durability



Air-conditioners, refrigerators, geysers, pumps etc. are often prone to burnouts because of overload & short circuit. This can be harmful for the appliance. The North-West Power Unit is a unique, compact unit providing protection to your appliances. It comprises of a Single Phase Motor Starter (for overload protection), a Double Pole MCB & a 25A Illuminated Plug & socket (with spring loaded tubes)



Power Unit Selection Guide

Appliance	Suitable Power Unit Rating(Amps)	Power Unit (with MCB)		Standard Power Unit (without MCB)	
		Box-Type Cat No.	Flush-Type Cat No.	Box-Type Cat No.	Flush-Type Cat No.
1/8 HP PUMP	0.60A - 1.00A	PPU 6M-BT A	PPU 6M-FT A	PPU 4M-BT A	PPU 4M-FT A
1/4 HP PUMP	0.90A - 1.50A	PPU 6M-BT B	PPU 6M-FT B	PPU 4M-BT B	PPU 4M-FT B
1/3 HP PUMP	1.20A - 2.00A	PPU 6M-BT C	PPU 6M-FT C	PPU 4M-BT C	PPU 4M-FT C
1/2HP PUMP	2.00A - 3.50A	PPU 6M-BT D	PPU 6M-FT D	PPU 4M-BT D	PPU 4M-FT D
3/4 HP PUMP	3.00A - 5.00A	PPU 6M-BT E	PPU 6M-FT E	PPU 4M-BT E	PPU 4M-FT E
1 TON A/C	4.75A - 7.50A	PPU 6M-BT F	PPU 6M-FT F	PPU 4M-BT F	PPU 4M-FT F
1.5 TON A/C	7.00A - 11.50A	ACPU 6M-BT G	ACPU 6M-FT G	ACPU 4M-BT G	ACPU 4M-FT G
2 TON A/C	11.00A - 18.00A	ACPU 6M-BT H	ACPU 6M-FT H	ACPU 4M-BT H	ACPU 4M-FT H
2.5 TON A/C	16.00A - 25.00A	ACPU 6M-BT J	ACPU 6M-FT J	ACPU 4M-BT J	ACPU 4M-FT J