

Battery Controller

LRC14ILBS

REMOTE CONTROL

STANDARD CARTON QUANTITY: 1
Operating Frequency 868.4 MHz

LIB1ICHA

1 GANG BATTERY CONTROLLER

Fully portable, can be used from any location in the system

Can be selected as the system's Primary Controller

RF Range up to 75m (open field)

Can control up to 64 devices in total

Pre programmed with ALL OFF function and HOLIDAY MODE function

Low battery indicator

Long battery life of up to 2 years (under normal operating conditions)

STANDARD CARTON QUANTITY: 1

Supplied with wall and back box mounting brackets, batteries and all required fixings.

Operating Frequency 868.4 MHz

Select the appropriate 1 Gang Dimmer Fascia for your Battery Controller Module.



LIB2ICHA

2 GANG BATTERY CONTROLLER

Fully portable, can be used from any location in the system

Can be selected as the system's Primary Controller

RF Range up to 75m (open field)

Can control up to 64 devices in total

Pre programmed with ALL OFF function and HOLIDAY MODE function

Low battery indicator

Long battery life of up to 2 years (under normal operating conditions)



STANDARD CARTON QUANTITY: 1

Supplied with wall and back box mounting brackets, batteries and all required fixings.

Operating Frequency 868.4 MHz

Select the appropriate 2 Gang Dimmer Fascia for your Battery Controller Module.

SUN ELECTRICALS (MK Honeywell)