

Dimmer Modules

LDM31IC

1 GANG 300W DIMMER MODULE

RF Range up to 75m (open field)
Can control up to 5 devices
Can control either a group or a scene
Pre programmed with HOLIDAY MODE function
Mains powered

STANDARD CARTON QUANTITY: 1

Suitable for use with the following load types and maximum load ratings only.

Load Type	1G 300W Dimmer
GLS	25-300W
Tungsten filament	25-300W
Tungsten halogen	25-300W
12V ELV Tungsten halogen with wirewound or electronic transformers	35-300W

Not suitable with any other load type. Do not use different types of lamps on the same load current.

BS EN 60669-2-1
BS EN 61000-6-1 / 3
ETSI EN 301489-1 / 2
ETSI EN 300220-1 / 2

Mounting Boxes: Flush Mounting 72 * 72 * 50

Operating Frequency 865.2 MHz

Select the appropriate 1 Gang Dimmer Fascia for your Dimmer Module

LDM32IC

2 GANG 300W DIMMER MODULE

RF Range up to 75m (open field)
Can control up to 5 devices
Can control either a group or a scene
Pre programmed with HOLIDAY MODE function
Mains powered

STANDARD CARTON QUANTITY: 1

Suitable for use with the following load types and maximum load ratings only.

<u>Load Type</u>	<u>2G 300W Dimmer</u>
GLS	25-300W per channel
Tungsten filament	25-300W per channel
Tungsten halogen	25-300W per channel
12V ELV Tungsten halogen with wirewound or electronic transformers	35-300W per channel

Not suitable with any other load type. Do not use different types of lamps on the same load current.

BS EN 60669-2-1
BS EN 61000-6-1 / 3
ETSI EN 301489-1 / 2
ETSI EN 300220-1/ 2

Mounting Boxes: Flush Mounting 72 * 72 * 50

Operating Frequency 865.2 MHz

Select the appropriate 2 Gang Dimmer Fascia for your Dimmer Module

LDM61IC

1 GANG 600W DIMMER MODULE

RF Range up to 75m (open field)
Can control up to 5 devices
Can control either a group or a scene
Pre programmed with HOLIDAY MODE function
Mains powered

STANDARD CARTON QUANTITY: 1

Suitable for use with the following load types and maximum load ratings only.

Load Type	1G 600W Dimmer
GLS	25-600W
Tungsten filament	25-600W
Tungsten halogen	25-600W
12V ELV Tungsten halogen with wirewound or electronic transformers	35-600W

Not suitable with any other load type. Do not use different types of lamps on the same load current.

BS EN 60669-2-1
BS EN 61000-6-1 / 3
ETSI EN 301489-1 / 2
ETSI EN 300220-1 / 2

Mounting Boxes: Flush Mounting 72 * 72 * 50

Operating Frequency 865.2 MHz

Select the appropriate 1 Gang Dimmer Fascia for your Dimmer Module